

SECTION TABLE OF CONTENTS

DIVISION 11 - EQUIPMENT

APPENDIX TO 11400 KITCHEN EQUIPEMENT

PART 1 NOT USED

PART 2 EQUIPMENT

PART 3 NOT USED

-- End of Section Table of Contents --

APPENDIX TO 11400 KITCHEN EQUIPEMENT

PART 1 NOT USED

PART 2 EQUIPMENT

ITEM NO.: 1 (1 SET) REQUIRED

ITEM: DISHTABLE, SOILED (MCAR)

MANUFACTURER: FABRICATOR

MODEL NO.: CUSTOM - SIZE AND SHAPE AS INDICATED AND SPECIFIED.
PROVIDE:

- A. INTEGRAL STAINLESS STEEL SCRAPPING TROUGH [152 MM WIDE BY 89 MM][6" WIDE BY 3 1/2"] DEEP AT WATER INLET ENDS AND [127 MM][5"] DEEP AT DISPOSAL SINK END. TROUGH TO BE INTEGRALLY WELDED TO DISPOSAL SINK
- B. DISPOSAL SINK [508 MM WIDE X 508 MM WIDE X 203 MM DEEP][20" WIDE X 20" WIDE X 8" DEEP]. DISPOSAL (ITEM # 4) COLLAR TO BE WELDED INTEGRALLY TO DISPOSAL SINK
- C. HOLE FOR VACUUM BREAKER TO BE MOUNTED THROUGH BACKSPLASH
- D. HOLE(S) FOR PRE-RINSE ASSEMBLY (ITEM # 5) THROUGH BACKSPLASH
- E. BRACKET FOR DISPOSAL (ITEM #4) CONTROLS

ITEM NO.: 2 (1) REQUIRED
 ITEM: SILVER SOAK SINK (OMAR)
 MANUFACTURER: PIPER PRODUCTS INC
 MODEL NO.: 337-3474

STD FEATURES:
 A. LEVER HANDLE DRAIN
 B. STAINLESS STEEL

ACCESSORIES:
 A. SILVER CHUTE

ITEM NO.: 3 (1) REQUIRED
ITEM: OVERHEAD RACK SHELF, SLANTED (MCAR)
MANUFACTURER: FABRICATOR
MODEL NO.: CUSTOM - SIZE AND SHAPE AS INDICATED AND SPECIFIED.
PROVIDE:

A. APPROXIMATELY [1575 MM LONG, 535 MM WIDE][62" LONG, 21"
WIDE] MINIMUM, TO ACCOMMODATE THREE [508 X 508 MM][20" X
20"] DISHWASHER RACKS, WALL MOUNTED

ITEM NO.: 4 (1) REQUIRED
ITEM: GARBAGE DISPOSER (MCAR)
MANUFACTURER: HOBART
MODEL NO.: FD3-300-D-2 (208/60/3)

STD FEATURES:

- A. DUAL DIRECTIONAL GRINDING
- B. HARDENED AND REPLACEABLE STAINLESS STEEL CUTTER BLOCKS

ACCESSORIES:

- A. GROUP D ACCESSORIES, INCLUDES NITRITE RUBBER
SILVER-SAVER SPLASH GUARD RING, [178 MM][7"] I.D.
STAINLESS STEEL WELD-IN ADAPTER FOR SINK, FIXED DIRECTION
WATER INLET FOR SINK AND VACUUM BREAKER
- B. GROUP 2 ELECTRIC CONTROL INCLUDES MAGNETIC CONTACTORS,
PUSHBUTTON START AND STOP AUTOMATIC REVERSING, NEMA 12
ENCLOSURE AND SOLENOID VALVE

ITEM NO.: 5 (3) REQUIRED
ITEM: PRE-RINSE SPRAY ASSEMBLY (MCAR)
MANUFACTURER: T & S BRASS AND BRONZE WORK
MODEL NO.: B-0113

STD FEATURES:

- A. CENTER BACKSPLASH MOUNTED FAUCET
- B. [457 MM][18"] RISER
- C. SPRAY VALVE
- D. FINGER HOOK
- E. [863 MM][34"] STAINLESS STEEL HOSE LENGTH

ACCESSORIES:

- A. WALL BRACKET
- B. VACUUM BREAKER

ITEM NO.: 6 (1) REQUIRED
ITEM: CONDENSING HOOD (MCAR)
FOR DISHWASHER ITEM # 7
(SEE MECHANICAL DRAWINGS AND SPECIFICATIONS)

MANUFACTURER: GREENHECK

MODEL NO.: GC

STD FEATURES:

- A. REMOVABLE CONDENSATE BAFFLES
- B. FULL PERIMETER WELDED GUTTER
- C. STAINLESS STEEL DRAIN
- D. ALL [1.3 MM][18 GAUGE] STAINLESS STEEL CONSTRUCTION

ACCESSORIES:

- A. NONE

ITEM NO.: 7 (1) REQUIRED
ITEM: DISHWASHER (MCAR)
MANUFACTURER: HOBART
MODEL NO.: AM-14

STD FEATURES:

- A. [ELECTRIC IMMERSION HEAT] [GAS IMMERSION HEAT]
- B. LED DISPLAYS (FILL, WASH, RINSE) AND TEMPERATURE
- C. LOW WATER CONSUMPTION - [4.5 LITERS][1.2 GALLONS] PER RACK
- D. 1 H.P. MAGNETICALLY CONTROLLED MOTOR
- E. STAINLESS STEEL
- F. STRAIGHT-THROUGH OPERATION WITH THIRD DOOR FOR INSPECTION
- G. FEATURES FLEXIBLE TIMING FOR SPECIAL APPLICATIONS

ACCESSORIES:

- A. FIVE EACH HEAVY DUTY ALL-PLASTIC PEG COMPARTMENT RACK, [508 MM X 508 MM][20" X 20"]
- B. FIVE EACH HEAVY DUTY ALL-PLASTIC COMBINATION RACK, [508 MM X 508 MM][20" X 20"]

ITEM NO.: 8 (1) REQUIRED
ITEM: BOOSTER HEATER (MCAR)
FOR DISHWASHER ITEM # 7
MANUFACTURER: HATCO
MODEL NO.: #C-12

STD FEATURES:

- A. "PILOT LIGHT"
- B. ON AND OFF SWITCH
- C. LOW WATER CUT-OFF
- D. HEATING CAPACITY [454 LPH][120 GPH] FOR [4.4-DEGREE C][40-DEGREE F] TEMPERATURE RISE
- E. [22.7 LITER][6 GALLON] STORAGE CAPACITY

ACCESSORIES:

- A. ALL STAINLESS STEEL BODY AND BASE
- B. [150 TO 190 MM][6" TO 7 1/2"] ADJUSTABLE STAINLESS STEEL LEGS

ITEM NO.: 9 (1) REQUIRED
EM: OVERHEAD SHELF, FLAT (MCAR)
MANUFACTURER: FABRICATOR
MODEL NO.: CUSTOM - SIZE AND SHAPE AS INDICATED AND SPECIFIED.
PROVIDE:
A. APPROXIMATELY [1070 MM LONG, 535 MM WIDE MINIMUM][42" LONG,
21" WIDE]
B. WALL MOUNTED

ITEM NO.: 10 (1 SET) REQUIRED
ITEM: CLEAN DISHTABLE (MCAR)
MANUFACTURER: FABRICATOR
MODEL NO.: CUSTOM - SIZE AND SHAPE AS INDICATED AND SPECIFIED.

ITEM NO.: 11 (2) REQUIRED
ITEM: HAND SINK (MCAR)
(SEE PLUMBING SPECIFICATIONS)

MANUFACTURER:
MODEL NO.:

STD FEATURES:

- A. STAINLESS STEEL SINK
- B. WRIST ACTION FAUCET

ACCESSORIES:

- A. SOAP AND TOWEL DISPENSER WITH MIRROR (SEE TOILET ACCESSORY SECTION)

ITEM NO.: 12 (3) REQUIRED
 ITEM: AIR CURTAIN (MCAR)
 MANUFACTURER: MARS
 MODEL NO.: 42C

STD FEATURES:

- A. WALL MOUNTED CONTROL PANEL FOR ONE (1) MOTOR, MOUNTED ON
 WALL RIGHT OF DOOR
- B. WHITE FINISH

ACCESSORIES:

NONE

ITEM NO.: 13 (1) REQUIRED
ITEM: CAN WASH (MCAR)
(SEE CIVIL AND PLUMBING DRAWINGS)
MANUFACTURER:
MODEL NO.: CUSTOM - SIZE AND SHAPE AS INDICATED AND SPECIFIED.

ITEM NO.: 14 (1) REQUIRED
ITEM: BOOSTER HEATER (MCAR)
FOR 3-COMPARTMENT SINK ITEM # 17
MANUFACTURER: HATCO
MODEL NO.: #C-15

STD FEATURES:

- A. "PILOT LIGHT"
- B. ON AND OFF SWITCH
- C. LOW WATER CUT-OFF
- D. HEATING CAPACITY [571.6 LPH FOR 4.4-DEGREE C]
[151 GPH FOR 40-DEGREE F] TEMPERATURE RISE
- E. [22.7 LITER][6 GALLON] STORAGE CAPACITY

ACCESSORIES:

- A. ALL STAINLESS STEEL BODY AND BASE
- B. [150 TO 200 MM][6" TO 8"] ADJUSTABLE STAINLESS STEEL LEGS

ITEM NO.: 15 (1) REQUIRED
ITEM: SANITIZING SINK HEATER (MCAR)
FOR 3-COMPARTMENT SINK ITEM # 17
MANUFACTURER: HATCO
MODEL NO.: 3CS-9

STD FEATURES:

- A. ON AND OFF SWITCH WITH INDICATING LIGHT
- B. ENERGY CUT-OFF WIRED INTO THE ELECTRICAL CIRCUIT
- C. DUAL RESERVOIR SYSTEM
- D. SIDE DRAIN
- E. SANITIZING TEMPERATURE INDICATOR
- F. LOW WATER LIGHT
- G. BALANCED 3-PHASE ELECTRICAL POWER

ACCESSORIES:

- A. ALL STAINLESS STEEL BODY AND BASE
- B. RINSE TEMPERATURE MONITOR

NOTE:

- A. MOUNTED UNDER RINSE COMPARTMENT OF 3-COMPARTMENT SINK, ITEM # 17

ITEM NO. 16 (1 SET) REQUIRED
ITEM: CONDENSING HOOD (MCAR)
FOR 3-COMPARTMENT SINK, ITEM # 17
(SEE MECHANICAL DRAWINGS AND SPECIFICATIONS)

MANUFACTURER: GREENHECK

MODEL NO.: GC

STD FEATURES:

- A. REMOVABLE CONDENSATE BAFFLES
- B. FULL PERIMETER WELDED GUTTER
- C. STAINLESS STEEL DRAIN
- D. ALL [1.31 MM][18 GAUGE] STAINLESS STEEL CONSTRUCTION

ACCESSORIES:

NONE

ITEM NO. 17 (1 SET) REQUIRED
ITEM: SINK, 3-COMPARTMENT (MCAR)
MANUFACTURER: FABRICATOR
MODEL NO.: CUSTOM - SIZE AND SHAPE AS INDICATED AND SPECIFIED.
PROVIDE:

- A. BRACKET FOR DISPOSAL (ITEM #18) CONTROLS
- B. DISPOSAL CONE SINK (ACCESSORY WITH ITEM #18)
INTEGRALLY WELDED TO DRAINBOARD
- C. HOLES FOR PRE-RINSE ASSEMBLY (ITEM # 5) AND
VACUUM BREAKER IN BACKSPLASH
- D. TWO FAUCETS (SEE PLUMBING SPECIFICATION)
- E. DRAIN ASSEMBLY EACH COMPARTMENT
- F. HOT TAP FAUCET AT RINSE COMPARTMENT (SEE
PLUMBING SPECIFICATION)
- G. I.D. PLATE "WARNING 180-DEGREE F WATER" MOUNTED
ON BACKSPLASH AT RINSE COMPARTMENT

ITEM NO.: 18 (1) REQUIRED
ITEM: GARBAGE DISPOSER (MCAR)
FOR 3-COMPARTMENT SINK ITEM # 17
MANUFACTURER: HOBART
MODEL NO.: FD3-300-B-2 (208/60/3)

STD FEATURES:

- A. DUAL DIRECTIONAL GRINDING
- B. HARDENED AND REPLACEABLE STAINLESS STEEL CUTTER BLOCKS

ACCESSORIES:

- A. CONE SINK [381 MM][15"] I.D. WITH HOLE FOR WATER SWIRL INLET
- B. GROUP B ACCESSORIES INCLUDES NITRITE RUBBER SILVER-SAVER
SPLASH GUARD RING, WATER SWIRL AND VACUUM BREAKER
- C. GROUP 2 ELECTRIC CONTROL INCLUDES MAGNETIC CONTACTORS,
PUSHBUTTON START AND STOP AUTOMATIC REVERSING, NEMA 12
ENCLOSURE AND SOLENOID VALVE

ITEM NO.: 19 (1) REQUIRED
ITEM: WARMING CABINET (OMAR)
MANUFACTURER: ALTO-SHAM
MODEL NO.: 1000-UP SERIES

STD FEATURES:

- A. TWO ON/OFF ADJUSTABLE THERMOSTATS 60-200-DEGREE F,
ONE FOR EACH COMPARTMENT
- B. TWO HOLDING TEMPERATAURE GAUGES TO MONITOR
- C. TWO CHROME PLATED SIDE RACKS DESIGNED TO ACCOMMODATE
STANDARD FULL SIZE PANS
- D. THREE CHROME PLATED WIRE SHELVES FOR FULL SIZE SHEET PANS
- E. HALO HEAT SYSTEM
- F. ALL STAINLESS STEEL CONSTRUCTION
- G. TWO INDICATOR LIGHTS
- H. DOUBLE COMPARTMENT HOLDING CABINET
- I. ONE SET OF 5" HEAVY DUTY CASTERS WITH BRAKES

ACCESSORIES:

NONE

ITEM NO.: 20 (1) REQUIRED
ITEM: MIXER (OMAR)
MANUFACTURER: HOBART
MODEL NO.: A-200-DT

STD FEATURES:

- A. STAINLESS STEEL BOWL GUARD
- B. 1/2 H.P. MOTOR
- C. 15-MINUTE TIMER
- D. THREE FIXED SPEEDS
- E. [18.9 LITER][20 QUART] STAINLESS STEEL BOWL
- F. FLAT "B" BEATER
- G. "D" WIRE LOOP WHIP
- H. [1830 MM][6'] CORD AND PLUG

ACCESSORIES:

- A. DELUXE FINISH

ITEM NO.: 21 (1) REQUIRED
ITEM: MIXER STAND (OMAR)
FOR MIXER ITEM # 20
MANUFACTURER: PIPER PRODUCTS INC
MODEL NO.: MX-29-TSS

STD FEATURES:

- A. STAINLESS STEEL UNDERSHELF
- B. STAINLESS STEEL LEGS

ACCESSORIES:

- A. MX-52-R STAINLES STEEL ACCESSORY RACK
- B. MODIFY STAINLESS STEEL LEG WITH BULLET FEET #331-3429

ITEM NO.: 22 (1) REQUIRED
ITEM: CONVECTION OVEN (MCAR)
MANUFACTURER: VULCAN-HART
MODEL NO.: VC66GD

STD FEATURES:

- A. DOUBLE SECTION, DEEP DEPTH GAS CONVECTION OVENS
- B. STAINLESS STEEL FRONT AND LEGS
- C. ADJUSTABLE FEET
- D. INDEPENDENTLY OPERATED STAINLESS STEEL 180-DEGREE-SWING DOORS WITH WINDOWS, 2(TWO) PER SECTION
- E. 44,000 BTU/H BURNER PER SECTION; 88,000 BTU/H TOTAL INPUT
- F. ELECTRONIC SPARK IGNITERS
- G. 1/2 HP TWO SPEED OVEN BLOWER-MOTOR PER SECTION, 115/60/1
- H. FRONT, SIDE MOUNTED SOLID STATE TEMPERATURE CONTROLS; RANGE [65.5 TO 260-DEGREE C][150 TO 500-DEGREES F]
- I. 60-MINUTE TIMER WITH AUDIBLE ALARM
- J. AUXILIARY FAN SWITCH FOR RAPID COOL DOWN
- K. TWO INTERIOR OVEN LIGHTS PER SECTION
- L. COOL TOUCH DOOR HANDLES
- M. STAINLESS STEEL OVEN DOOR GASKETS
- N. ELEVEN-POSITION NICKEL PLATED RACK GUIDES WITH POSITIVE RACKS TOPS PER OVEN
- O. FIVE HEAVY DUTY NICKEL PLATED RACKS PER OVEN
- Q. SINGLE [19 MM][3/4"] GAS CONNECTION WITH MANUAL SHUT-OFF VALVE AND REGULATOR

ACCESSORIES:

- A. STAINLESS STEEL DRIP PANS
- B. STAINLESS STEEL INTERIOR
- C. STAINLESS STEEL SIDES AND TOP
- D. STAINLESS STEEL REAR BODY ENCLOSURE PANEL

ITEM NO.: 23 (1) REQUIRED
ITEM: RANGE WITH OVEN (MCAR)
MANUFACTURER: VULCAN-HART
MODEL NO.: GH45

STD FEATURES:

- A. HEAVY DUTY FOUR BURNER GAS RANGE WITH STANDARD OVEN
- B. STAINLESS STEEL FRONT
- C. STAINLESS STEEL FRONT TOP LEDGE
- D. [152 MM][6"] STAINLESS STEEL ADJUSTABLE LEGS WITH BULLET FEET
- E. [32 MM][1 1/4"] DIAMETER FRONT GAS MANIFOLD
- F. FOUR 30,000 BTU/H HEAVY CAST TWO PIECE "FLAME RETENTION" BURNERS WITH INDIVIDUAL PILOTS AND CONTROL VALVES
- G. HEAVY CAST IRON AERATION PLATES WITH DEEP BOWLS AND REMOVABLE CAST TOP GRATES
- H. OVEN CONTROLS LOCATED IN COOL ZONE
- I. OVEN IS PORCELAIN ENAMEL ON STEEL HEARTH, DOOR AND SIDE LINERS, [660.4 MM W X 711.2 MM D X 355.6 MM H] [26" W X 28" D X 14" H]
- J. ONE OVEN RACK
- K. TWO RACK POSITIONS
- L. 50,000 BTU/H HEAVY CAST "FLAME RETENTION" BURNER WITH ELECTRONIC PILOT IGNITION
- M. OVEN TEMPERATURE RANGE: [65.5 TO 260-DEGREES C] [150 TO 500-DEGREES F]

ACCESSORIES:

- A. STAINLESS STEEL SIDES
- B. [19 MM][3/4"] REAR GAS CONNECTION
- C. "BG" SERIES [430 MM][17"] HIGH STAINLESS STEEL BACKGUARD

ITEM NO.: 24 (1) REQUIRED
 ITEM: STEAM JACKETED KETTLE (MCAR)
 MANUFACTURER: CLEVELAND RANGE INC
 MODEL NO.: KGT-12-T

STD FEATURES:

- A. [45.4 LITER][12 GALLON] SELF CONTAINED GAS TILTING KETTLE
- B. TEMPERATURE RANGE: [63 TO 127-DEGREE C][145 TO 260-DEGREE F]
- C. "SPLASH PROOF" SOLID STATE CONTROL PANEL FOR TEMPERATURE, LOW WATER AND POWER ON/OFF SWITCH WITH L.E.D. INDICATORS FOR HEAT CYCLE AND LOW WATER WARNING
- D. KETTLE AND ALL EXTERIOR SURFACES STAINLESS STEEL WITH #4 FINISH
- E. ENERGY EFFICIENT (65%), HIGH PERFORMANCE GAS-FIRED HEATING SYSTEM FOR FAST HEAT UP AND RECOVERY TIME, 53,000 BTU FIRING RATE AND 34,5000 BTU DIRECTLY APPLIED TO THE PRODUCT
- F. GAS PRESSURE REGULATOR
- G. SELF LOCKING MARINE-TYPE TILTING MECHANISM WITH BALANCED DESIGN FOR EASY TILTING, TILT HANDLE MOUNTED AT RIGHT, DOUBLE SAFETY GAS SHUT OFF TURNS OFF GAS WHEN UNIT IS TILTED
- H. LARGE HEAVY DUTY, ROLLED RIM POURING LIP
- I. "SPLASH PROOF" RECESSED PRESSURE/VACUUM GAUGE
- J. STEAM JACKET PERMANENTLY FILLED WITH TREATED DISTILLED WATER (VENTING AND/OR REFILLING NOT REQUIRED), 50 PSI STEAM JACKET RATING WITH SAFETY VALVE MOUNTED TOWARD THE REAR OF KETTLE
- K. AUTOMATIC ELECTRONIC SPARK IGNITION SYSTEM
- E. HINGED STAINLESS STEEL DOOR
- F. [1830 MM][6'] CORD AND PLUG, 5 AMPS

ACCESSORIES:

- A. MODEL NUMBER ST-28 EQUIPMENT STAND - ALL STAINLESS STEEL CONSTRUCTION WITH REMOVABLE SLIDING COMBINATION DRAIN DRAWER (WITH SPLASH SHIELD) AND PAN SUPPORTS, [31.75 MM][1 1/4"] SQUARE TUBING, ADJUSTABLE FEET (REAR FEET WITH FLANGE)
- B. HOT AND COLD WATER FAUCET (DPK) WITH BRACKET (FBKT)
- C. 316 STAINLESS STEEL LINER (316G)
- D. LIFT OFF COVER (CL)
- E. SELF LOCKING HAND TILT MECHANISM (HTK)
- F. KETTLE MARKINGS (KM)

ITEM NO.: 25 (1) REQUIRED
 ITEM: BRAISING PAN (MCAR)
 MANUFACTURER: VULCAN-HART
 MODEL NO.: VG40

STD FEATURES:

- A. [152 LITER][40 GALLON] GAS TILTING BRAISING PAN
- B. ONE 30,000 BTU/H BURNER PER EACH [304.8 MM][12"] PAN WIDTH, 120,000 BTU/H TOAL INPUT
- C. BURNERS SHUT OFF WHEN PAN IS TILTED 5-DEGREES
- D. PAN MAY BE FULLY TILTED SO PAN MAY BE EMPTIED COMPLETELY
- E. PAN BODY [2 MM][14 GAUGE] STAINLESS STEEL, FRONT HINGED, INTERIOR COVED BOTTOM AND CORNERS WITH ETCHED GALLON MARKINGS
- F. COOKING SURFACE STAINLESS STEEL BONDED TO [13 MM][1/2"] THICK CARBON STEEL PLATE
- G. FULL WIDTH FRONT TYPE FORMED POURING LIP FLANGED [102 MM][4"] ON BOTH SIDES WITH REMOVABLE POURING LIP STRAINER
- H. DROP AWAY FOOD PAN RECEIVING SUPPORT MOUNTS UNDER POURING LIP
- I. STAINLESS STELL SPRING ASSIST ONE PIECE COVER WITH FULL WIDTH HANDLE AND FULL WIDTH REAR DRIP LIP, LIFT ASSIST WILL HOLD COVER OPEN AT ANY POSITION, CONDENSATE LIP ON COVER TO REDUCE DRIP
- J. WATER TIGHT CONTROLS AND ENCLOSURES
- K. MANUALLY OPERATED PAN TILTING MECHANISM WITH FULL WIDTH STAINLESS STEEL BAR FOLDING SWING-AWAY HANDLE
- L. ELECTRONIC IGNITION SYSTEM FOR AUTOMATIC BURNER LIGHT
- M. 60-MINUTE TIMER
- N. ON/OFF LIGHTED ROCKER SWITCH
- O. ONE SNAP ACTING THERMOSTAT ADJUSTABLE FROM [37.7 TO 232-DEGREES C][100 TO 450-DEGREES F]
- P. [19 MM][3/4"] REAR GAS CONNECTION AND GAS PRESSURE REGULATOR
- Q. BASED ENCLOSED BY LIFT OFF PANELS, BOX TYPE CONSTRUCTION
- R. [305 MM][12"] STAINLESS STEEL [50 MM][2"] DIAMETER LEGS WITH STAINLESS STEEL ADJUSTABLE FEET, FEET FLANGED
- S. EXPOSED EXTERIOR STAINLESS STEEL
- T. CSA DESIGN CERTIFIED, CLASSIFIED BY UL TO NSF STD. # 4
- U. [1830 MM][6'] CORD AND PLUG, 120/60/1, 3 AMPS

ACCESSORIES:

- A. [305MM] [12"] DOUBLE JOINTED DOUBLE JPANTRY FAUCET

ITEM NO.: 26 (1) REQUIRED
ITEM: DRAIN TROUGH (MCAR)
(SEE PLUMBING SPECIFICATIONS)
MANUFACTURER:
MODEL NO.:

ITEM NO.: 27 (1) REQUIRED
ITEM: HOOD OVER COOKING AREA (MCAR)
FOR CONVECTION OVEN ITEM # 22,
RANGE W/ OVEN ITEM # 23,
TILTING KETTLE ITEM # 24,
AND BRAISING PAN ITEM # 25
(SEE MECHANICAL DRAWINGS AND SPECIFICATIONS)

MANUFACTURER: GREENHECK

MODEL NO.: GHAW

STD FEATURES:

- A. UL LISTED FULL COMPENSATING EXHAUST HOOD WITH AIR CURTAIN SUPPLY
- B. UL LISTED VAPORPROOF INCANDESCENT LIGHTS
- C. FIRE DAMPER IN SUPPLY DUCT COLLAR
- D. FULL LENGTH GREASE TROUGH WITH REMOVABLE GREASE CONTAINER
- E. SIZE AS INDICATED

ACCESSORIES:

- A. ALL [1.6 MM][16 GAUGE] STAINLESS STEEL CONSTRUCTION
- B. STAINLESS STEEL BAFFLE-TYPE REMOVABLE GREASE FILTERS
- C. WATER FIRE SUPPRESSION SYSTEM

ITEM NO.: 28 (2) REQUIRED
ITEM: WORK TABLE, MOBILE (OMAR)
MANUFACTURER FABRICATOR
MODEL NO.: CUSTOM - SIZE AND SHAPE AS INDICATED AND SPECIFIED.
PROVIDE:

- A. FOUR [127 MM][5"] DIAMETER NON-MARKING, BALL BEARING, STEM-TYPE CASTERS
- B. TWO CASTERS WITH LOCKING BRAKES
- C. [508 MM X 508 MM X 127 MM][20" X 20" X 5"] DEEP STAINLESS STEEL DRAWER WITH REMOVABLE INSET

ITEM NO.: 29 (1) REQUIRED
 ITEM: HOT FOOD WELL (OMAR)
 MANUFACTURER: SERVOLIFT/EASTERN STEEL
 MODEL NO.: 501-4

STD FEATURES:

- A. 900 WATT HEATING SYSTEM FOR EACH FOOD PAN WELL WITH ADJUSTABLE CONTROL THERMOSTAT WITH "OFF" POSITION AND NEON PILOT LIGHT
- B. FOUR [127 MM][5"] DIAMETER, HEAVY DUTY, DOUBLE BALL BEARING SWIVEL CASTERS WITH NON-MARKING RUBBER TIRES
- C. TWO CASTERS WITH BRAKES
- D. REMOVABLE [1500 MM][5 FOOT] CORD AND PLUG SET
- E. [250 MM][10"] ALUMINUM FRONT AND END APRONS WITH FACTORY BONDED VINYL FABRIC (COLOR SELECTION BELOW)

ACCESSORIES:

- A. FOOD PROTECTOR, "CODE FP"
- B. FOOD WELLS WITH INDIVIDUAL DRAINS MANIFOLDED TO ONE [20 MM][3/4"] DRAIN VALVE
- C. CAM-ACTION LATCHES WITH TRIGGER RELEASE (USED TO JOIN MULTIPLE UNITS TOGETHER)
- D. FRONT AND END APRON COLOR - [NEUTRA][ROYAL BLUE][CARDINAL RED][WALNUT]

[DESIGNER NOTE: IF ROLL-UP DOOR (TO THE FLOOR) IS USED INSTEAD OF ROLL-UP WINDOW (TO THE WINDOWSILL) ADD THE FOLLOWING OPTION AND DO NOT USE ITEM # 41, STAINLESS STEEL TRAY SLIDE.]

- E. [SOLID RIBBED STYLE TRAY SLIDE, "CODE ST"]

[DESIGN NOTE: IF HOT FOOD WELL ITEM #29 TO BE USED WHERE FLOOR DRAIN IS NOT AVAILABLE (SUCH AS IF USED IN AN ASSEMBLY AREA) INCLUDE ACCESSORY #F.]

- F. PROVIDE HOSE TO ALLOW DRAINING UNIT INTO A CONTAINER (BUCKET)

ITEM NO.: 30 (1) REQUIRED
 ITEM: COLD FOOD UNIT (OMAR)
 MANUFACTURER: SERVOLIFT/EASTERN STEEL
 MODEL NO.: 502-3RCW

STD FEATURES:

- A. COLD WALL FOOD UNIT
- B. FOUR [127 MM][5"] DIAMETER, HEAVY DUTY, DOUBLE BALL BEARING SWIVEL CASTERS WITH NON-MARKING RUBBER TIRES
- C. TWO CASTERS WITH BRAKES
- D. MECHANICAL REFRIGERATION
- E. NEMA 5-15P PLUG WITH [1500 MM][5 FOOT] THREE-WIRE CORD UL LISTED
- F. [13 MM][1/2"] STAINLESS STEEL DRAIN WITH SHUT-OFF VALVE
- G. [250 MM][10"] ALUMINUM FRONT AND END APRONS WITH FACTORY BONDED VINYL FABRIC (COLOR SELECTION BELOW)

ACCESSORIES:

- A. DISPLAY CASE, DOUBLE DECK, "CODE DC"
- B. CAM-ACTION LATCHES WITH TRIGGER RELEASE (USED TO JOIN MULTIPLE UNITS TOGETHER)
- C. FRONT AND END APRON COLOR - [NEUTRA][ROYAL BLUE][CARDINAL RED][WALNUT]

[DESIGNER NOTE: IF ROLL-UP DOOR (TO THE FLOOR) IS USED INSTEAD OF ROLL-UP WINDOW (TO THE WINDOWSILL) ADD THE FOLLOWING OPTION AND DO NOT USE ITEM # 41, STAINLESS STEEL TRAY SLIDE.]

- D. [SOLID RIBBED-STYLE TRAY SLIDE, "CODE ST"]

[DESIGN NOTE: IF COLD FOOD WELL UNIT ITEM #30 TO BE USED WHERE FLOOR DRAIN IS NOT AVAILABLE (SUCH AS IF USED IN AN ASSEMBLY AREA) INCLUDE ACCESSORY #F.]

- F. PROVIDE HOSE TO ALLOW DRAINING UNIT INTO A CONTAINER (BUCKET)

ITEM NO.: 31 (1) REQUIRED
ITEM: SLICER (OMAR)
MANUFACTURER: HOBART
MODEL NO.: 2712

STD FEATURES:

- A. TWO SPEED AUTOMATIC CARRIAGE SLICER WITH FRONT MOUNTED CONTROLS AND REMOVABLE TILTING CARRIAGE SYSTEM
- B. TWO SPEED CARRIAGE DRIVE 52 STROKES PER MINUTE FOR HIGH SPEED; 36 STROKES PER MINUTE FOR SLOW SPEED
- C. CONTOURED CAST STAINLESS STEEL "STAY SHARP" KNIFE WITH SANITARY HUB
- D. ANTIMICROBIAL PRODUCT PROTECTION
- E. CAPACITY UP TO [305 MM][12"] WIDE OR [190 MM][7 1/2"] DIAMETER
- F. ADJUSTABLE STAINLESS STEEL FENCE
- G. LIFETIME GUARANTEED, TOP MOUNTED REMOVABLE AND SUBMERSIBLE BORAZON STONE SHARPENER
- H. DOUBLE-ACTION INDEXING CAM
- I. PERMANENTLY MOUNTED KNIFE RING GUARD
- J. HEAVY GAUGE STAINLESS STEEL TOP COVER WITH INTEGRATED PRODUCT DEFLECTOR
- K. LIFT LEVER
- L. REMOVABLE REAR DEFLECTOR
- M. ELECTROLESS NICKEL PLATED SINGLE SLIDE ROD WITH RESERVOIR WICK
- N. STAINLESS STEEL CARRIAGE, GAUGE PLATE AND KNIFE COVER
- O. ERGONOMIC STYLE HANDLE
- P. GAUGE PLATE WITH STAINLESS STEEL RIBBED FACE
- Q. LOW FENCE
- R. SANITARY BURNISHED ALUMINUM BASE
- S. NO TOOLS REQUIRED FOR PROPER CLEANING
- T. 1/2 HP PERMANENTLY LUBRICATED BALL BEARING KNIFE DRIVE MOTOR, SINGLE PHASE CAPACITOR-START, INDUCTION RUN
- U. NYLON CARRIAGE ROLLER
- V. HOBART POLY V-BELT KNIFE DRIVE, RUNS AT 400 RPM FOR OPTIMAL PERFORMANCE
- W. WARRANTY - ALL PARTS AND SERVICE FOR ONE YEAR INCLUDING KNIFE
- X. [1800 MM][6 FOOT] THREE-WIRED CORD AND PLUG

ACCESSORIES:

NONE

ITEM NO.: 32 (1) REQUIRED
ITEM: TABLE, FOOD PREPARATION (OMAR)
WITH POT & PAN RACK
MANUFACTURER: FABRICATOR
MODEL NO.: CUSTOM - SIZE AND SHAPE AS INDICATED AND SPECIFIED.
PROVIDE:

- A. CANTILEVER 2-BAR STAINLESS STEEL POT RACK
- B. POT RACK CONSTRUCTED OF [51 MM X 6 MM][2" X 1/4"] STAINLESS STEEL BARS WELDED TO ITS UPRIGHTS
- C. POT RACK WITH DOUBLE POINT STAINLESS STEEL SLIDING HOOKS 1 PER APPROXIMATELY EVERY [200 MM][8"]
- D. POT RACK SUPPORTED BY [41 MM][1 5/8"] O.D. [1.6 MM THICK][16 GAUGE] STAINLESS STEEL UPRIGHTS
- E. UPRIGHTS TO EXTEND THROUGH STAINLESS STEEL GUSSETS AND OPENING IN THE TABLE TOP
- F. [508 MM X 508 MM X 127 MM][20" X 20" X 5"] DEEP STAINLESS STEEL DRAWER WITH REMOVABLE INSET
- G. STAINLESS STEEL UNDERSHELF

ITEM NO.: 33 (1) REQUIRED
ITEM: CAN OPENER (OMAR)
MANUFACTURER: EDLUND
MODEL NO.: 270

STD FEATURES:

- A. REMOVABLE KNIFE AND KNIFE HOLDER (NO TOOLS REQUIRED)
- B. GEAR AND SHIELD DESIGNED TO PREVENT SPLASH-BACK FROM ENTERING INTERIOR (REMOVABLE WITHOUT TOOLS)
- C. HEAVY DUTY STAINLESS STEEL CONSTRUCTION
- D. TWO-SPEED MOTOR
- E. HIGH VOLUME CAPACITY
- F. WEIGHTED AND BALANCED TO LIFT HEAVIEST # 10 CAN
- G. UL LISTED
- H. NSF CERTIFIED
- I. 120/60/1, 1.2 AMPS

ACCESSORIES:

- A. NONE

ITEM NO.: 34 (2) REQUIRED
 ITEM: REFRIGERATOR (OMAR)
 MANUFACTURER: TRAULSEN
 MODEL NO.: RHT232WUT-FHS

STD FEATURES:

- A. STAINLESS STEEL FRONT HOUSING, ENDS AND DOORS
- B. STAINLESS STEEL INTERIOR
- C. THREE CHROME PLATED ADJUSTABLE SHELVES SUPPORTED ON
SHELF STUDS PER SECTION
- D. EXTERIOR DIGITAL THERMOMETER
- E. 10-FOOT THREE-WIRE CORD AND PLUG
- F. SELF CLOSING FULL LENGTH DOORS W/ STAY OPEN AT 120 DEGREES
- G. 5 YEAR COMPRESSOR WARRANTY
- H. GUARANTEED FOR LIFE CAM HINGES
- I. GUARANTEED FOR LIFE HORIZOANTAL WORK FLOW DOOR HANDLE
- J. AUTOMATICALLY ACTIVATED INCANDESCENT LIGHTS
- K. STAINLESS STEEL BREAKER CUPS

ACCESSORIES:

- A. 6" ADJUSTABLE STAINLESS STEEL LEGS AND FEET

ITEM NO.: 35 (1) REQUIRED
ITEM: FREEZER (OMAR)
MANUFACTURER: TRAULSEN
MODEL NO.: RLT132WUT-FHS

STD FEATURES:

- A. STAINLESS STEEL FRONT HOUSING, ENDS AND DOORS
- B. STAINLESS STEEL INTERIOR
- C. THREE HEAVY DUTY CHROME-PLATED WIRE SHELVES PER SECTION
- D. EXTERIOR DIGITAL THERMOMETER
- E. CONDENSING UNIT ON TOP W/AUTOMATIC NON-ELECTRIC CONDENSATE DISPOSAL
- F. R404A REFRIGERANT
- G. 10-FOOT THREE-WIRE CORD AND PLUG
- H. 6" ADJUSTABLE LEGS WITH STAINLESS STEEL FEET
- I. STANDARD OPERATING TEMPERATURE (0 TO -5 DEGREES F)
- J. FULL HEIGHT, SELF CLOSING DOORS W/STAY OPEN FEATURE
- K. AUTOMATIC ACTIVATED INCANDESCENT LIGHTS

ACCESSORIES:

- A. [150 MM][6"] ADJUSTABLE LEGS WITH STAINLESS STEEL FEET

ITEM NO.: 36 (1) REQUIRED
ITEM: ICE MACHINE (MCAR)
MANUFACTURER: MANITOWOC ICE INC
MODEL NO.: Q-MODEL SERIEC 450, #QD-0452A

STD FEATURES:

- A. DICE CUBE SIZE, [173 KGS][380 lbs]/24HR
- B. AIR COOLED
- C. R404A REFRIGERANT
- C. 3/4 H.P. COMPRESSOR
- D. STAINLESS STEEL FINISH

ACCESSORIES:

- A. S-400 STAINLESS STEEL BIN WITH POLYETHYLENE SEAMLESS BIN LINER

ITEM NO.: 37 (3) REQUIRED
ITEM: MOBILE RACK (OMAR)
MANUFACTURER: CRES COR
MODEL NO.: 100-1841C

STD FEATURES:

- A. MULTI-PURPOSE STORAGE CABINETS OF NON-CORROSIVE ALUMINUM
- B. FULL LENGTH REINFORCED DOOR SWINGS 270-DEGREES
- C. CARD CLIP INCLUDED TO LATCH DOOR TO SIDE OF CABINET
- D. HOLDS [457 MM X 660 MM][18" X 26"] PAN ON [38 MM][1 1/2"] CENTERS
- E. HEAVY DUTY [127 MM][5"] SWIVEL CASTERS WITH NEOPRENE TIRES; BEARINGS SEALED AND PERMANENTLY LUBRICATED
- F. FRONT CASTERS WITH BRAKES

ACCESSORIES:

- A. ONE PIECE WRAP AROUND, REINFORCED, NON-MARKING RUBBER BUMPER, ADDS [51 MM][2"] TO WIDTH AND DEPTH, MODEL NUMBER 1405-0000

ITEM NO.: 38 (5) REQUIRED
ITEM: SHELVING (OMAR)
MANUFACTURER: SERVOLIFT/EASTERN STEEL
MODEL NO.: SERIES 80-S

STD FEATURES:

- A. APPROXIMATE SIZE: [1070 MM L X 460 MM W X 1625 MM H]
[42" L X 18" W X 64" H]
- B. TWO "FREE STANDING" UNITS AND THREE "ADD ON" UNITS REQUIRED
- C. ANGLE BEARER CLIPS (USED TO CONNECT MULTIPLE SECTIONS)
- D. [1.3 MM][18 GAUGE] STAINLESS STEEL SOLID-STYLE SHELVES,
FIVE PER EACH UNIT
- E. SHELVES WITH [32 MM][1 1/4"] HIGH STOP LEDGE ON REAR
- F. ADJUSTABLE SANITARY BULLET FEET

ACCESSORIES:

- A. [25 MM][1"] O.D. STAINLESS STEEL UPRIGHTS WITH TOP CAPS

ITEM NO.: 39 (1 SET) REQUIRED
ITEM: VEGETABLE SINK (MCAR)
MANUFACTURER: FABRICATOR
MODEL NO.: CUSTOM - SIZE AND SHAPE AS INDICATED AND SPECIFIED.
PROVIDE:

- A. ONE FAUCET (SEE PLUMBING SPECIFICATION)
- B. DRAIN ASSEMBLY EACH COMPARTMENT
- C. GOOSE-NECK SPRAY ASSEMBLY WITH WALL BRACE, SEE ITEM # 5

ITEM NO.: 40 (2) REQUIRED
 ITEM: TRAY BUSING RACK, DOUBLE (OMAR)
 MANUFACTURER: CRES COR
 MODEL NO.: [2213-1824][_____] (see Notes)

STD FEATURES:

- A. APPROXIMATE SIZE: [1070 MM W X 770 MM D X 1770 MM H]
 [____ MM W X ____ MM D X ____ MM H][(42" W X 30" D X
 69 1/2" H)][(____" W X ____" D X ____" H]
- B. TRAY BUSSING RACK OF NON-CORROSIVE ALUMINUM
- C. EXTRUDED CHANNELS RIVETED IN PLACE AND SPACED [130 MM]
 [5 1/8"] ON CENTER
- D. CHANNELS DESIGNED TO SECURELY HOLD TRAY TOP AND BOTTOM
 (TRAY WILL NOT TIP IF HALF WAY OUT OF THE CHANNEL)
- E. HEAVY DUTY [127 MM][5"] SWIVEL CASTERS WITH NEOPRENE TIRES;
 BEARINGS SEALED AND PERMANENTLY LUBRICATED
- F. FRONT CASTERS WITH BRAKES

ACCESSORIES:

- A. SIDE ENCLOSURES
- B. BACK ENCLOSURE
- C. BOTTOM ENCLOSURE
- D. ONE PIECE WRAP AROUND, REINFORCED, NON-MARKING RUBBER
 BUMPER, ADDS [51 MM][2"] TO WIDTH AND DEPTH

NOTES:

- A. VERIFY TRAY SIZE WITH CONTRACTING OFFICER BEFORE ORDERING
 ITEM TO ENSURE CORRECT MODEL NUMBER IS ORDERED
- B. ITEM SHALL BE FROM THE SAME MANUFACTURER AS ITEM # 44
 DISPENSER, CUP AND GLASS, AND ITEM # 45 DISPENSER,
 SILVERWARE/TRAY, WITH THE SAME SONSTRUCTION AND STYLING

[DESIGNER NOTE: Verify tray size selected by user with Contracting Officer.
 A different model number will need to be selected if tray size does not fit
 this rack. Designer will need to fill in the blanks for STD FEATURES "A" and
 verify information in STD FEATURES "C" if different model rack is to be used.]

ITEM NO.: 41 (1) REQUIRED
ITEM: STAINLESS STEEL TRAY SLIDE (MCAR)
MANUFACTURER: FABRICATOR
MODEL NO.: CUSTOM - SIZE AND SHAPE AS INDICATED AND SPECIFIED.
PROVIDE:

- A. STAINLESS STEEL SOLID-STYLE TRAY SLIDE
- B. TRAY SLIDE SURFACE RIBBED

NOTE:

- A. WIDTH INCLUDES WALL/WINDOW SILL THICKNESS

[DESIGNER NOTE: COORDINATE USE OF ITEM # 41 TRAY SLIDE WITH OPTIONS USED ON ITEM # 29 HOT FOOD WELL AND ITEM # 30 COLD FOOD UNIT. IF ROLL-UP DOOR (TO THE FLOOR) IS USED INSTEAD OF ROLL-UP WINDOW (TO THE WINDOWSILL), ITEM # 41 TRAY SLIDE WILL NOT BE NEEDED AND A TRAY SLIDE OPTION IS TO BE ADDED TO BOTH ITEMS # 29 AND # 30.]

ITEM NO.: 42 (1) REQUIRED
ITEM: COFFEE URN (MCAR)
MANUFACTURER: WILBUR CURTIS COMPANY INC
MODEL NO.: RU-150

STD FEATURES:

- A. AUTOMATIC COFFEE URN, SINGLE MODEL [11 LITER][3 GALLON] CAPACITY
- B. AUTOMATIC REFILL DURING BREWING CYCLE
- C. THERMOSTATICALLY CONTROLLED FOR NEAR-INSTANT RECOVERY
- D. CLOSED LID BREWING
- E. SWING-SPRAY HEAD
- F. ELECTRIC OPERATION
- G. STAINLESS STEEL FILTER BASKET WITH HOLD-DOWN FLAPS
- H. AUTOMATIC AGITATOR/AERATOR
- I. MANUAL AGITATOR/AERATOR
- J. EMERGENCY REFILL
- K. BREWS [49 LITERS][13 GALLONS] COFFEE PER HOUR
- L. UL LISTED
- M. NSF APPROVED
- N. HOT WATER FAUCET

ACCESSORIES:

- A. DOUBLE CHECK VALVE
- B. HALF BREW CYCLE
- C. EVERPURE WATER FILTER
- D. LOW WATER CUT OFF THERMOSTAT

ITEM NO.: 43 (1) REQUIRED
 ITEM: DRINK STAND, W/ DOLLY (MCAR)
 MANUFACTURER: FABRICATOR
 MODEL NO.: CUSTOM - SIZE AND SHAPE AS INDICATED AND SPECIFIED.
 PROVIDE:

- A. STAINLESS STEEL CONSTRUCTION
- B. [610 MM][24"] (APPROXIMATELY) WIDE DOORS, 1 PAIR, APPROXIMATELY RIGHT 2/3 WIDTH OF UNIT
- C. [457 MM][18"] (APPROXIMATELY) WIDE DOORS, 1 PAIR, APPROXIMATELY LEFT 1/3 WIDTH OF UNIT
- D. FULL LENGTH DRIP TRAY APPROXIMATELY [100 MM W X 100 MM D] [4" W X 4" D] WITH [25 MM][1"] NPT DRAIN
- E. OPEN BOTTOM RIGHT 2/3 OF UNIT (BEHIND PAIRED [610 MM][24"] WIDE DOORS)
- F. CLOSED BOTTOM LEFT 1/3 OF UNIT (BEHIND PAIRED [457 MM][18"] WIDE DOOR) WITH INTERMEDIATE SHELF
- G. ONE EACH [254 MM WIDE BY 127 MM HIGH][10" WIDE BY 5" HIGH] CUTOUT IN BACK OF STAND (FOR ACCESS TO ELECTRICAL OUTLET AND PLUMBING CONNECTIONS)
- H. ONE EACH STAINLESS STEEL DOLLY MINIMUM OF [660 MM WIDE X 660 MM DEEP X 381 MM HIGH][26" WIDE X 26" DEEP X 15" HIGH] (TO ACCOMMODATE FIVE SYRUP TANKS) WITH FOUR [50 MM][2"] MINIMUM DIAMETER NON-MARRING CASTERS
- I. FULL-LENGTH SOLID RIBBED TRAY SLIDE [33 MM][13"] WIDE
- J. TWO EACH [9.5 MM][1/4"] GROMMETED HOLES FOR WATER LINES CONNECTED TO COFFEE URN (ITEM # 42) AND SODA DISPENSER (NIC)
- K. TWO GALVANIZED EYELETS RATED FOR [68 Kg][150 LBS] WITH [25 MM][1"] I.D. LOCATED INSIDE UNIT IN FRONT LEFT CORNER LOCATED TO ACCOMMODATE CHAIN FOR SECURING CO2 TANK

NOTE:

- A. ELECTRIC OUTLET ON WALL ABOVE STAND FOR COFFEE MAKER ITEM # 42
- B. ELECTRIC OUTLET ON WALL BELOW COUNTER TOP AT BACK OF STAND FOR SODA DISPENSER (NIC)
- C. HOSE BIB ON WALL BELOW COUNTER TOP AT BACK OF STAND FOR WATER CONNECTIONS TO COFFEE URN #42 AND SODA DISPENSER (NIC)

ITEM NO.: 44 (3) REQUIRED
 ITEM: DISPENSER, CUP AND GLASS (OMAR)
 MANUFACTURER: SERVOLIFT
 MODEL NO.: ACCA-ST-20 X 20

STD FEATURES:

- A. CANTILEVER STYLE, MOBILE, ADJUSTABLE CUP AND DISPENSER, [584 MM W X 787 MM D X 940 MM H]
 [___ MM W X ___ MM D X ___ MM H]
 [23" W X 31" D X 37" H] [___" W X ___" D X ___" H]
- B. DISPENSING MECHANISM RAISED BY A SERIES OF COIL SPRINGS ATTACHED TO THE FRAME; BALL BEARING GUIDES AND 1 STEEL AIRCRAFT TYPE CABLE KEEP RACK CARRIER LEVEL EVEN WITH UNEVEN LOAD; CABLE RUNS OVER PRE-LUBRICATED PLATED STEEL PULLEYS
- C. APPROXIMATE CAPACITY: UP TO 192 GLASSES OR 175 CUPS
- D. STAINLESS STEEL TUBULAR PUSH HANDLE
- E. FRAME IS ALL-WELDED HEAVY GAUGE STEEL FINISHED WITH GRAY BAKED ENAMEL OVER RUST-RESISTING UNDERCOAT; MOUNTED ON [1.2 MM][12 GAUGE] STAINLESS STEEL "Z" SECTION BASE
- F. BODY IS [2 MM][20 GAUGE] STAINLESS STEEL ON ALL SIDES AND TOP
- G. RACK CARRIER IS ALL-WELDED [1.6 MM][16 GAUGE] STAINLESS STEEL
- H. FRONT PANEL REMOVABLE FOR ADJUSTMENT ACCESS

ACCESSORIES:

- A. HEAVY DUTY [127 MM][5"] SWIVEL DOUBLE BALL BEARING CASTERS WITH NON-MARKING RUBBER TIRES
- B. BACK TWO CASTERS WITH BRAKES
- C. ONE PIECE WRAP AROUND, REINFORCED, NON-MARKING RUBBER BUMPER, ADDS [51 MM][2"] TO WIDTH AND DEPTH
- D. FOR [508 MM X 508 MM][___ MM X ___ MM][20" X 20"] [___" X ___"] SIZE DISHWASHER RACKS

NOTES:

- A. VERIFY DISHWASHER RACK SIZE WITH CONTRACTING OFFICER BEFORE ORDERING ITEM TO ENSURE CORRECT MODEL NUMBER IS ORDERED, ESPECIALLY IF THE CONTRACTOR SUBSTITUTES A DIFFERENT MANUFACTURER/MODEL NUMBER DISHWASHER ITEM # 7 THAN THE MANUFACTURER/MODEL NUMBER LISTED
- B. ITEM SHALL BE FROM THE SAME MANUFACTURER AS ITEM # 40 TRAY BUSING RACK, DOUBLE, AND ITEM # 45, DISPENSER, SILVERWARE/TRAY, WITH THE SAME CONSTRUCTION AND STYLING.

[DESIGNER NOTE: Actual model number to be ordered shall be based on dishwasher rack size. Designer will need to fill in the blanks for STD FEATURES "A" and ACCESSORIES "D" if different dishwasher Item # 7 and dishwasher rack size is used.]

ITEM NO.: 45 (2) REQUIRED
 ITEM: DISPENSER, SILVERWARE/TRAY (OMAR)
 MANUFACTURER: SERVOLIFT
 MODEL NO.: ATCA-ST-OSW8 TRAY SIZE [[356 X 457 MM] [14" X 18"]]
 TRAY SIZE [[___ X ___ MM] [___" X ___"]]

STD FEATURES:

- A. CANTILEVER STYLE, MOBILE, ADJUSTABLE TRAY AND SILVERWARE DISPENSER, [[483W X 737D X 1295MM H] [19"W X 29"D X 51"H] FOR TRAY SIZE [356 x 457MM] [14" x 18"]]
 [[___W X ___D X 1295MM H] [___"W X ___"D X 51"H] FOR TRAY SIZE [___ X ___MM] [___" X ___"]]
- B. TOP MOUNTED STAINLESS STEEL SLOPED OVERHEAD-TYPE SILVERWARE DISPENSER, ENCLOSED ON ALL FOUR SIDES WITH EIGHT OPENINGS FOR ROUND SILVERWARE CYLINDERS
- C. DISPENSING MECHANISM RAISED BY A SERIES OF COIL SPRINGS ATTACHED TO THE FRAME; BALL BEARING GUIDES AND 1 STEEL AIRCRAFT TYPE CABLE KEEP RACK CARRIER LEVEL EVEN WITH UNEVEN LOAD; CABLE RUNS OVER PRE-LUBRICATED PLATED STEEL PULLEYS
- D. APPROXIMATE CAPACITY: 100 TO 150 TRAYS, 35 TO 40 PIECES OF SILVERWARE PER CYLINDER
- E. FRAME IS ALL-WELDED HEAVY GAUGE STEEL FINISHED WITH GRAY BAKED ENAMEL OVER RUST-RESISTING UNDERCOAT; MOUNTED ON [1.2 MM][12 GAUGE] STAINLESS STEEL "Z" SECTION BASE
- F. BODY IS [2 MM][20 GAUGE] STAINLESS STEEL ON ALL SIDES AND TOP
- G. TRAY CARRIER IS ALL-WELDED [1.6 MM][16 GAUGE] STAINLESS STEEL
- H. FRONT PANEL REMOVABLE FRO ADJUSTEMENT ACCESS

ACCESSORIES:

- A. HEAVY DUTY [127 MM][5"] SWIVEL DOUBLE BALL BEARING CASTERS WITH NON-MARKING RUBBER TIRES
- B. BACK TWO CASTERS WITH BRAKES
- C. ONE PIECE WRAP AROUND, REINFORCED, NON-MARKING RUBBER BUMPER, ADDS [51 MM][2"] TO WIDTH AND DEPTH
- D. EIGHT NYLON SILVERWARE CYLINDERS

NOTES:

- A. VERIFY TRAY SIZE WITH CONTRACTING OFFICER BEFORE ORDERING ITEM TO ENSURE CORRECT MODEL NUMBER IS ORDERED
- B. ITEM SHALL BE FROM THE SAME MANUFACTURER AS ITEM # 40 TRAY Busing Rack, DOUBLE, AND ITEM # 44, DISPENSER, CUP AND GLASS, WITH THE SAME CONSTRUCTION AND STYLING.

[DESIGNER NOTE: Actual item to be ordered shall be coordinated with Contracting Officer based on tray size selected by user. Designer will need to fill in the blanks for STD FEATURES "A" if different size tray is to be used.]

ITEM NO: 46 (1) REQUIRED
ITEM: GLASS FILLER (MCAR)
ADDED TO ASSEMBLY HALL EWC
(SEE PLUMBING DRAWINGS AND SPECIFICATIONS)
MANUFACTURER: T & S BRASS AND BRONZE WORKS
MODEL NO.: B1225

STD FEATURES:

- A. COMBINATION GLASS AND PITCHER FILLER
- B. PUSH BACK GLASS FILLER WITH VOLUME REGULATOR
- C. SWING NOZZLE FOR PITCHERS

ACCESSORIES:

NONE

[DESIGNER NOTE: Glass Filler Item # 46 may not be required if Drink Stand Item #43 with Coffee Urn Item # 42 and NIC soda dispenser are used as listed. (It is assumed that the NIC soda dispense will include a water dispensing button.) If different model coffee urn/maker is used or not included, and the NIC soda dispenser will not include a water dispensing button, a water cooler with glass filler should be included in the Assembly Hall.]

ITEM NO.: 47 (1) REQUIRED
ITEM: MAKE-UP AIR UNIT (KMAU-1) (MCAR)
AND KITCHEN FAN (KF-1)
FOR HOOD ITEM # 27
(SEE MECHANICAL DRAWINGS AND SPECIFICATIONS)

MANUFACTURER: GREENHECK

MODEL NO.: KSU ARRANGEMENT A

STD FEATURES:

A. AS INDICATED AND SPECIFIED

ACCESSORIES:

A. AS INDICATED AND SPECIFIED

PART 3 NOT USED

-- End of Section --